

# Lovibond® Colour Measurement Tintometer® Group



## AF327 Pt-Co/Hazen/APHA Colour, Low Range, 0 - 70 mg

Visual Colour Grading of Platinum-Cobalt/Hazen/APHA Colour (Range 0 - 70 mg)



- Complies with the Path Length Requirements of ASTM D 1209,
- Fast, Economical & Portable Visual Matching
- Two-Field Vision for Accurate Results
- Ability to Guarantee Constant Lighting Conditions

Part Number: 433270

### Enables You to Comply to ASTM 1209

The Lovibond® AF327 is a special kit for visual colour grading of Platinum-Cobalt/Hazen/APHA Colour over the range 0 - 70 mg Pt/l. It enables you to comply with the path length requirements of ASTM D 1209, which specifies a system for colour comparison where a 100 ml column of sample 275 - 295 mm in length is matched with Platinum-Cobalt solutions.

### Fast, Economical & Portable Visual Matching

The Comparator 2000+ is a flexible, modular system for Visual Colour Grading. Using a suitable comparator instrument and glass disc, you can quickly visually match the sample directly against the calibrated, colour stable glass standards.

### Two-Field Vision for Accurate Results

Lovibond® comparator instruments include an integrated prism which causes the sample and comparison fields to overlap, allowing enhanced colour discrimination and matching. The prism is ultrasonically sealed to prevent contamination of the optics. Each individually graded glass standard represents a discrete step on the measurement range (as opposed to a continuous graduation), aiding colour discrimination and allowing great accuracy of results.

### Ability to Guarantee Constant Lighting Conditions

An optional item for the Comparator 2000+ is the Daylight 2000 Lighting Unit. This is a standardised light source which guarantees you a constant lighting condition for accurate colour grading. This is particularly useful when the sample is very pale in colour. By using a Lovi-

bond® lighting unit, you can be confident of uniform lighting conditions for colour matching, 24 hours a day and irrespective of ambient lighting.

### Extended Shelf Life

The unique feature of Lovibond® test discs is that they incorporate coloured glass standards that are colour stable and not affected by UV light or extreme environmental conditions.

Please note, we cannot guarantee compatibility of discontinued Lovibond® Comparator 1000 disks with the Lovibond® 2000+ Comparator.

## Industry

Chemical Industry | Food and Beverage Industry | Oil and Gas | Pharmaceutical Industry

## Application

Chemicals | Edible Oils and Fats | Petroleum Oils and Waxes | Waste-Water Treatment

## AF327 Pt-Co/Hazen/APHA Colour, Low Range, 0 - 70 mg

The Lovibond® AF327 is a special kit for visual colour grading of Platinum-Cobalt/Hazen/APHA Colour over the range 0 - 70 mg Pt/l. It enables you to comply with the path length requirements of ASTM D 1209, which specifies a system for colour comparison where a 100 ml column of sample 275 - 295 mm in length is matched with platinum-cobalt solutions.

## Technical Data

**Applicable Standard** ASTM D1209  
ISO 6271

**Colour Type** Transparent

**Portability** Portable

## Delivery Scope

- 1 x Nessleriser Daylight 2000+
- 1 x Hazen D1209 0-30 Disc
- 1 x Hazen D1209 30-70 Disc
- 1 x 1209 Nessleriser body
- 1 x Pair Nessler Cylinders
- 1 x Deionised Water

### Tintometer GmbH

Lovibond® Water Testing  
Schleefstraße 8-12  
44287 Dortmund  
Tel.: +49 (0)231/94510-0  
Fax: +49 (0)231/94510-30  
sales@lovibond.com  
www.lovibond.com  
Germany

### The Tintometer Limited

Lovibond House  
Sun Rise Way  
Amesbury, SP4 7GR  
Tel.: +44 (0)1980 664800  
Fax: +44 (0)1980 625412  
sales@lovibond.uk  
www.lovibond.com  
UK

### Tintometer China

Room 1001, China Life Tower  
16 Chaoyangmenwai Avenue,  
Beijing, 100020  
Tel.: +86 10 85251111 App. 330  
Fax: +86 10 85251001  
chinaoffice@tintometer.com  
www.lovibond.com  
China

### Tintometer South East Asia

Unit B-3-12, BBT One Boulevard,  
Lebuh Nilam 2, Bandar Bukit Tinggi,  
Klang, 41200, Selangor D.E  
Tel.: +60 (0)3 3325 2285/6  
Fax: +60 (0)3 3325 2287  
lovibond.asia@tintometer.com  
www.lovibond.com  
Malaysia

### Tintometer Brazil

Caixa Postal: 271  
CEP: 13201-970  
Jundiaí – SP  
Tel.: +55 (11) 3230-6410  
sales@tintometer.com.br  
www.lovibond.com.br  
Brazil

### Tintometer Inc.

6456 Parkland Drive  
Sarasota, FL 34243  
Tel: 941.756.6410  
Fax: 941.727.9654  
sales@lovibond.us  
www.lovibond.com  
USA

### Tintometer India Pvt. Ltd.

Door No: 7-2-C-14, 2<sup>nd</sup>, 3<sup>rd</sup> & 4<sup>th</sup> Floor  
Sanathnagar Industrial Estate,  
Hyderabad, 500018  
Telangana  
Tel: +91 (0) 40 23883300  
Toll Free: 1 800 599 3891/ 3892  
indiaoffice@lovibond.in  
www.lovibondwater.in  
India

### Tintometer Spain

Postbox: 24047  
08080 Barcelona  
Tel.: +34 661 606 770  
sales@tintometer.es  
www.lovibond.com  
Spain

Technical changes without notice  
Printed in Germany

Lovibond® and Tintometer® are Trademarks of the Tintometer Group of Companies