

# Lovibond® Colour Measurement Tintometer® Group



## Model Fx

Benchtop spectrophotometer optimised for analysis of edible oils



- Guaranteed site-to-site comparability with accurate and precise spectrophotometry
- Avoid inconsistent readings with controlled sample temperature
- Ensure measurement consistency with easy to clean, removable sample chamber
- Save benchtop space in your QC laboratory with a smaller instrument footprint

Part Number: 169200

### Guaranteed Temperature Consistency

The Lovibond® Model Fx solves the temperature problems associated with consistently measuring the colour of edible oils and addresses the need for quickly delivering accurate results. If samples are not properly prepared before measurement, turbidity caused by the crystallisation of the samples will lead to inconsistent readings. The integrated sample cell heater ensures consistent and uniform temperature throughout the sample resulting in inaccurate measurements.

### Optimised for Production Environment

Reliable and repeatable test results are key to ensuring final product quality and minimise production costs. Speed of analysis is vital for efficient process control. The simplicity of operation helps reduce errors and increase productivity. The instrument's aluminium housing is chemical resistant and intended to withstand the hazards of the production environment.

### Save Costs, Misinterpretation and Potential Disputes

Suppliers and buyers need a common language to communicate and determine product quality. The Lovibond® Model Fx automatically reports key measurements to ensure that data is collected consistently and is reproducible by different users or across multiple sites. Should disagreement occur between supplier and customer, this additional information can help resolve any dispute, saving time and costs.

### Ensures Compliance to Standards

The Lovibond® Model Fx measures colour according to the Lovibond® RYBN, Lovibond® RY, Lovibond® RY10:1, AOCS Tintometer® RY, Chlorophyll & Beta-Carotene scales which are commonly used in the Edible Oil Industry. The accuracy, repeatability and reproducibility of data provided by the instrument allow for tighter colour specifications and greater colour consistency, giving companies the confidence needed to make important decisions regarding high-value commodities and refining operations.

### Industry

Chemical Industry | Food and Beverage Industry | Industries Others | Oil and Gas

### Application

Edible Oils and Fats

### Model Fx

The Lovibond® Model Fx solves the temperature problems associated with consistently measuring the colour of edible oils and addresses the need for quickly delivering accurate results. Misreading from crystallisation can be eliminated with its ability to keep the oil at a constant temperature and report the temperature of the sample.

## Technical Data

<b>Applicable Standard</b>	AOCS Cc 8d-55 AOCS Cc 13b-45 AOCS Cc 13d-55 AOCS Cc 13e-92 AOCS Cc 13j-97 BS684 BS684 Section 2.20 Chinese GB/T 22460-2008 IS 548 (part 1)-2010 ISO 15305 ISO 27608 MS 252 : Part 16 MS 817 : Part 12
<b>Colour Type</b>	Transparent
<b>Wavelength Range</b>	380 - 780 nm
<b>Wavelength Accuracy</b>	0.2 nm
<b>Spectral Scope</b>	< 15 nm
<b>Photometric Range</b>	0 - 100 % T
<b>Photometric Linearity</b>	± 0.01 % T
<b>Stray Light</b>	< 0.01 % T
<b>Detector</b>	Spectrometer
<b>Interfaces</b>	USB RS 232
<b>Instrument Housing</b>	Aluminium
<b>Repeatability</b>	± 0.5 % T
<b>Portability</b>	Benchtop
<b>Touchscreen</b>	No
<b>Input Voltage</b>	110 VAC, 250 VAC, 60 W (24 V)
<b>Environmental Conditions</b>	Temperature: +5°C - 40°C ; Humidity: Up To 90 % non condensing
<b>Stock Conditions</b>	Temperature: -20°C - 85°C ; Humidity: Up To 90 % non condensing
<b>Compliance</b>	CE
<b>Languages User Interface</b>	English, German, French, Spanish, Italian, Portuguese, Russian, Japanese, Chinese
<b>Dimensions</b>	301 x 152 x 331 mm
<b>Weight</b>	5.16 kg

## Accessories

Title	Part Number
W600/B/10 Borosilicate Glass	655960
W600/B/25 Borosilicate Glass	655990
W600/B/33 Borosilicate Glass	656010
W600/B/40 Borosilicate Glass	656020
W600/B/100 Borosilicate Glass	656030
W600/B/1/16" Borosilicate Glass	656044
W600/B/1/8" Borosilicate Glass	656054
W600/B/1/4" Borosilicate Glass	656064
W600/B/1/2" Borosilicate Glass	656074
W600/B/1" Borosilicate Glass	656080
W600/B/2" Borosilicate Glass	656090
W600/B/3" Borosilicate Glass	656104
W600/B/4" Borosilicate Glass	656114
W600/B/5" Borosilicate Glass	656124
W600/B/5 1/4" Borosilicate Glass	656130
W600/B/50 Borosilicate Glass	656200

## Delivery Scope

- Model Fx instrument
- External power supply
- Set of 3 power leads (UK, European and United States)
- Quick start guide (hard copy)
- USB memory stick (containing the manuals)
- Certificate of conformity
- Conformance filter
- W600/B/1" cell (Borosilicate, 1" path length)
- W600/B/5¼" cell (Borosilicate, 5¼" path length)

---

**Tintometer GmbH**

Lovibond® Water Testing  
Schleefstraße 8-12  
44287 Dortmund  
Tel.: +49 (0)231/94510-0  
Fax: +49 (0)231/94510-30  
sales@lovibond.com  
www.lovibond.com  
Germany

**The Tintometer Limited**

Lovibond House  
Sun Rise Way  
Amesbury, SP4 7GR  
Tel.: +44 (0)1980 664800  
Fax: +44 (0)1980 625412  
sales@lovibond.uk  
www.lovibond.com  
UK

**Tintometer China**

Room 1001, China Life Tower  
16 Chaoyangmenwai Avenue,  
Beijing, 100020  
Tel.: +86 10 85251111 App. 330  
Fax: +86 10 85251001  
chinaoffice@tintometer.com  
www.lovibond.com  
China

**Tintometer South East Asia**

Unit B-3-12, BBT One Boulevard,  
Lebuh Nilam 2, Bandar Bukit Tinggi,  
Klang, 41200, Selangor D.E  
Tel.: +60 (0)3 3325 2285/6  
Fax: +60 (0)3 3325 2287  
lovibond.asia@tintometer.com  
www.lovibond.com  
Malaysia

**Tintometer Brazil**

Caixa Postal: 271  
CEP: 13201-970  
Jundiaí – SP  
Tel.: +55 (11) 3230-6410  
sales@tintometer.com.br  
www.lovibond.com.br  
Brazil

**Tintometer Inc.**

6456 Parkland Drive  
Sarasota, FL 34243  
Tel: 941.756.6410  
Fax: 941.727.9654  
sales@lovibond.us  
www.lovibond.com  
USA

**Tintometer India Pvt. Ltd.**

Door No: 7-2-C-14, 2<sup>nd</sup>, 3<sup>rd</sup> & 4<sup>th</sup> Floor  
Sanathnagar Industrial Estate,  
Hyderabad, 500018  
Telangana  
Tel: +91 (0) 40 23883300  
Toll Free: 1 800 599 3891/ 3892  
indiaoffice@lovibond.in  
www.lovibondwater.in  
India

**Tintometer Spain**

Postbox: 24047  
08080 Barcelona  
Tel.: +34 661 606 770  
sales@tintometer.es  
www.lovibond.com  
Spain

Technical changes without notice  
Printed in Germany

Lovibond® and Tintometer® are Trademarks of the Tintometer Group of Companies