# Lovibond® Colour Measurement

## Tintometer® Group



## Petroleum Oils Comparator (AF650)

ASTM Oils Scale, 3-Field Visual Measurement



- Accurate Determination of the ASTM Oils Scale
- The AF 650 incorporates 16 glass standards which make up the scale in a pair of discs

#### Fast Determination of Colour Value

You can directly compare the sample with the colour values for quick

#### Easy to Achieve Optimum Colour Accuracy

The advantage of a 3-section field of view is that the sample and two consecutive glasses on the colour scale are viewed simultaneously, making it easier and quicker for you to achieve the ideal colour match.

#### Facilitates Tolerance Level Setting

For rapid colour grading within predetermined colour limits, the glass standards can be set to the two limiting colours so that it is easy to check that the sample is within tolerance.

#### **Guaranteed Constant Lighting Conditions**

In the instruments, the tungsten halogen light source is colour corrected to CIE standard illuminant C\*, which guarantees constant lighting conditions for colour grading.

#### Compliance to Standards

Each Comparator 3000 is supplied with the correct cells for the appropriate path length determined by the standard.

- Compact, Visual Measurement System for Single Scale Measurements
- Self-Contained, Includes Everything Needed to Measure the Scale
- Easy-To-Use, Fast & Accurate
- 3-Field Viewing for Optimum Accuracy

Part Number: 345030

<sup>\*</sup> In the EBC version, the C filter is replaced by the B filter as required by the standards.

#### Industry

Oil and Gas

#### Application

Petroleum Oils and Waxes

#### Petroleum Oils Comparator (AF650)

A 3-field instrument for visually determining the colour of petroleum oils & waxes samples according to the ASTM Color scale by direct comparison with coloured glass filters.

#### **Technical Data**

Applicable Standard ASTM D1500

ASTM D6045 ISO 2049

Colour Type Transparent
Portability Benchtop

### **Delivery Scope**

Comparator 3000

─**─** 1 Pair glass discs

- 0.5, 1.5, 2.5, 3.5, 4.5, 5.5, 6.5, 7.5 1.0, 2.0, 3.0, 4.0, 5.0, 6.0, 7.0, 8.0

— 3 x Cylindrical glass sample jars

#### **Tintometer GmbH**

Lovibond® Water Testing Schleefstraße 8-12 44287 Dortmund Tel.: +49 (0)231/94510-0 Fax: +49 (0)231/94510-30 sales@lovibond.com www.lovibond.com Germany

#### Tintometer Brazil Caixa Postal: 271

Calxa Postal. 271 CEP: 13201-970 Jundiaí – SP Tel.: +55 (11) 3230-6410 sales@tintometer.com.br www.lovibond.com.br Brazil

#### The Tintometer Limited

Lovibond House Sun Rise Way Amesbury, SP4 7GR Tel.: +44 (0)1980 664800 Fax: +44 (0)1980 625412 sales@lovibond.uk www.lovibond.com UK

#### Tintometer Inc.

6456 Parkland Drive Sarasota, FL 34243 Tel: 941.756.6410 Fax: 941.727.9654 sales@lovibond.us www.lovibond.com USA

#### **Tintometer China**

Room 1001, China Life Tower 16 Chaoyangmenwai Avenue, Beijing, 100020 Tel.: +86 10 85251111 App. 330 Fax: +86 10 85251001 chinaoffice@tintometer.com www.lovibond.com China

#### Tintometer India Pvt. Ltd.

Door No: 7-2-C-14, 2nd, 3rd & 4th Floor Sanathnagar Industrial Estate, Hyderabad, 500018 Telangana Tel: +91 (0) 40 23883300 Toll Free: 1 800 599 3891/3892 indiaoffice@lovibond.in www.lovibondwater.in India

#### **Tintometer South East Asia**

Unit B-3-12, BBT One Boulevard, Lebuh Nilam 2, Bandar Bukit Tinggi, Klang, 41200, Selangor D.E Tel.: +60 (0)3 3325 2285/6 Fax: +60 (0)3 3325 2287 lovibond.asia@tintometer.com www.lovibond.com Malaysia

#### Tintometer Spain

Postbox: 24047 08080 Barcelona Tel.: +34 661 606 770 sales@tintometer.es www.lovibond.com Spain

Technical changes without notice Printed in Germany Lovibond® and Tintometer® are Trademarks of the Tintometer Group of Companies