Lovibond[®] Colour Measurement

Tintometer® Group



Lighting Cabinets: TLC 60 / TLC 120

- Render colour more accurately every time
- 6 different light sources to detect any potential illuminant metameric failure
- Meets major international standards for visual colour measurement including: ASTM D1729, ISO3664, DIN, ANSI and BSI
- Easy to operate each light source has its own switch
- Timing meter to track optimum lamp replacement
- Quick and reliable no warm-up time
- Highly efficient economic power consumption and heat generation

Market sectors
Textiles and Dyeing
Packaging
Leather
Inks
Knitwear
Plastics
Automotive
Ceramics

Lighting Cabinets: TLC 60 / TLC 120



| Light Source | Light Simulation | Colour Temperature |
|--------------|---|--------------------|
| F | Tungsten (Illuminant A) | 2800 |
| D65 | International Standard Indirect Daylight | 6500 |
| TL84 | Applied to Stores in Europe, Japan & China | 4000 |
| UV | Ultraviolet Light (detects and evaluates optical brighteners or fluorescent pigments) | λ365 |
| CWF | Cool White Fluorescent (American Standard) | 4150 |
| TL83/U30 | Warm White Fluorescent | 3000 |

Artificial light found in retail environments around the world varies according to the technology being used. A different light source means a different perception of colour but it can also change the colour of one of two matching items so that they no longer match. This is called Illuminant Metamerism, and it can mean for example that a pair of trousers and jacket that match under one light source do not match under another. It would obviously be good to know this before large scale production.

The TLC 60 / 120 lighting cabinets provide a wide range of controlled lighting environments to view a product as others see it. At the touch of a button you can move from Tungsten to cool white or warm white fluorescent and achieve consistent visual colour assessment.

| Specifications | TLC 60 | TLC 120 |
|--------------------------|----------------------------------|----------------------------------|
| Configured Light Sources | F, D65, TL84, UV, CWF, TL83/ U30 | F, D65, TL84, UV, CWF, TL83/ U30 |
| Weight | 38Kg | 65Kg |
| Dimensions (mm) | 710 x 530 x 570 | 1310 x 600 x 800 |

| Order No | Product |
|----------|--|
| 403055 | Lovibond [®] TLC 60 Lighting Cabinet |
| 403060 | Lovibond [®] TLC 120 Lighting Cabinet |

| www.lovibond.com | sales@tintometer.com | 😑 Download form |
|-----------------------------|------------------------------|-----------------------------|
| The Tintometer Ltd | Tintometer Inc | Tintometer GmbH |
| T: +44 (0)1980 664800 | T: +1 941 756 6410 | T: +49 (0) 231/94510-0 |
| F: +44 (0)1980 625412 | F: + 1941 727 9654 | F: +49 (0) 231/94510-20 |
| Tintometer – China | Tintometer – South East Asia | Tintometer India Pvt. Ltd |
| T: +86 10 8525 1111 Ext 330 | T: +603 3325 2286 | T: +91 (0) 40-23883300 |
| F: +86 10 85251001 | F: +603 3325 2287 | Toll Free: 1800 599 3891/92 |

Lovibond[®] and Tintometer[®] are Registered Trade Marks of The Tintometer[®] Group. All translations and transliterations of LOVIBOND[®] & TINTOMETER[®] are asserted as Trade Marks of The Tintometer Limited. Registered Office: Lovibond House, UK. Registered in England No. 45024. Errors and Omissions Excepted – Content Subject to alterations without notice.

The Bluetooth® mark, figure mark and combination mark are trademarks owned by the Bluetooth SIG and any use by the Tintometer® Group is under license. Please note, Bluetooth® is not available for all regions. Please contact the local Lovibond® representative for details.